

PRODUCT SPECIFICATION & TECHNICAL DATASHEET

A400 - PVC Knitwrist

Collection: General Handling **Range:** Hand Protection **Materials:** Cotton, Polyester

Dipping:

Inner Pack: 12 Outer Carton: 144

Product information

The PVC Knitwrist fully dipped working glove with knitted wrist and cotton interlock lining. It has a smooth finish with the highest abrasion resistance rating. The fully dipped glove allows for advanced water and oil protection.



General Handling

The general handling and grip glove category is one of the most popular collections within the Portwest hand protection range. A carefully selected range of coatings, including latex, nitrile, polyurethane and PVC, provides a broad range of styles suited to a diverse range of tasks.

Hand Protection

A wide and increasing range of hand protection products is available. In order to help cater to every need. Only the best materials and manufacturing methods are used in the production of Portwests' extensive range of Hand Protection products....

Standards

EN ISO 21420: 2020 Dexterity 5 EN 388: 2016 + A1: 2018 (4121X) ANSI/ISEA 105: 2016 CUT Level (A1)



Features

- Fully coated for maximum liquid protection
- Phthalate Free
- Extremely flexible PVC
- Superb abrasion and tear resistance
- Knitted cuff for comfort and warmth
- ANSI cut level A1
- CE certified



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

A400 - PVC Knitwrist

Commodity Code: 6116108091

Test House

SATRA Technology Europe Ltd (Notified Body No.: NB: 2777)

Bracetown Business Park

D15 YN2P, Ireland

Cert No: 2777/19908-01/E00-00

SATRA Technology Centre Ltd (Notified Body No.: AB: 0321)

SATRA Technology Park NN16 8SD, United Kingdom

Cert No: AB0321/20181-01/E00-00

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	DUN14
A400BKRM	Black	41.0	28.0	50.0	0.1140	0.0574	5036108301850	15036108762566
A400BKRL	Black	41.0	28.0	50.0	0.1160	0.0574	5036108301843	15036108762559
A400BKRXL	Black	41.0	28.0	50.0	0.1600	0.0574	5036108301867	15036108762573
A400BKRXXL	Black	41.0	28.0	50.0	0.1400	0.0574	5036108301874	15036108762580

