

PRODUCT SPECIFICATION & TECHNICAL DATASHEET

P371 - ERGONET FFP3 Valved Dolomite

Respirator (Pk5)

Collection: Disposable Mask FFP3

Range: Disposable Masks Materials: PP, EVA Foam

Inner Pack: 5 Outer Carton: 30



Ergonomically designed to fit most face shapes, this respirator has a soft outer net cover to protect and retain its shape. Its high performing exhalation valve works efficiently to reduce heat and moisture inside the mask and provides comfort when used in hot and humid conditions. Other features include an innovative moulded nose bridge for a perfect fit, allround foam gasket and wide adjustable elastic head straps.



Disposable Mask FFP3

Disposable mask FFP3 level, protects against solid and liquid particles of high toxicity. Minimal % of filtration 99%. Protects up to 20 times the TLV (Assigned Protection Factor for FFP3 masks) or up to 50 times TLV (Nominal Protection Factor for FFP3 masks). Examples of applications: Sanding of hard wood (beech, oak) / treatment of wood using copper, chrome or arsenic based products / impact stripping of paint / sanding of cement. Our Biztex brand ensures exceptional quality and performance across our full range of disposable masks.

Disposable Masks

Our Biztex® brand ensures exceptional quality and performance across our full range of disposable masks. The extensive Biztex® range offers a high level of protection and quality safeguarding the wearer against many workplace risks including liquid chemicals, static electricity, dry particles and radioactive contamination. The complete Biztex® range includes disposable masks and limited-life garments.

Standards

EN 149 FFP3 (NR D)

Features

- Ergonet supports the mask structure and keeps the filter media clean
- \bullet Internal foam gasket ensures a tight face seal
- Soft nose bridge for a secure and comfortable fit
- Wide adjustable head straps for ultimate wearer comfort
- Non-magnetic nickel and ferrous free
- High performance exhalation valve to reduce heat and provide comfort when used in hot and humid conditions
- Dolomite optional clogging test (D) to provide more comfortable breathing and longer lasting filtration performance
- Retail box which aids presentation for retail sales
- CE certified
- UKCA marked
- CE-CAT III



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

P371 - ERGONET FFP3 Valved Dolomite Respirator (Pk5) Commodity Code: 6307909311

Test House

INSPEC International B.V. (Notified Body No.: NB: 2849)

Beechavenue 54 - 62

, Netherlands

Cert No: PPE20162100

INSPEC International B.V. (Notified Body No.: NB: 2849)

Beechavenue 54 - 62

, Netherlands

Cert No: UKCA-B-221228

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	DUN14
P371WHR	White	45.0	42.0	57.0	0.4100	0.1077	5036108285143	15036108775290

