

# THRYM VV736



ACRYLIC POLYAMIDE GLOVE - LATEX-COATED HAND - FOAM LATEX COATED PALM Model VV736





#### Product specifications

Inside: 100% acrylic gauge 10. Outside: 100% polyamide gauge 15. Full latex coating of the hand. Second foam latex coating on palm and fingertips.

Support: polyamide/ acrylic.

Coating: Latex.

#### COLOUR

Blue-Black

#### SIZE

09, 10, 11



Product Features and Benefits						
<b>0</b> % DMF						
•	Double full latex coating	1st smooth latex coating : waterproof 2nd foam latex coating : good adhesion				
***	Very good resistance to cold and humidity	Ideal in cold environments down to -30°C				
7	Brushed acrylic support	Maintenance of warmth during outdoor work Great comfort of use				
*	Also available with header card DPVV736					
	The versatility of the protection make these gloves real assets in all climatic circumstances!					



#### Certifications and Standards

# CE

#### **REGULATION (EU) 2016/425**

#### EN ISO 21420:2020 General requirements

#### EN388:2016+A1:2018 Protective gloves against mechanical Risks (Levels obtained on the palm)



- 2: Resistance to abrasion (from 1 to 4)
- 2: Resistance to cutting (from 1 to 5)
- 3: Resistance to tear (from 1 to 4)
- 1: Resistance to puncture (1 to 4)
- B: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)



#### EN511:2006 Protective gloves against cold (X = Unrealized test)

- 1: Resistance to convective cold (from 1 to 4)
- 2: Resistance to contact cold (from 1 to 4)
- 1: Waterproof (0 or 1)



## EN407:2020 Protective gloves against Heat (X = Unrealized test)

- X: Flame spread resistance (X).
- 2: Contact heat resistance (from 1 to 2)
- X: Convective heat resistance (1 to 2)
- X: Radiant heat resistance (from 1 to 2)
- X: Small splashes of molten metal (from 1 to 2)
- X: Large quantities of molten metal (from 1 to 2)



#### REGULATION 2016/425 PERSONAL PROTECTIVE EQUIPEMENT, AS AMENDED TO APPLY IN GB

# EN ISO 21420:2020 General requirements

### EN388:2016+A1:2018 Protective gloves against mechanical Risks (Levels obtained on the palm)



- 2: Resistance to abrasion (from 1 to 4)
- 2: Resistance to cutting (from 1 to 5)
- 3: Resistance to tear (from 1 to 4)
- 1: Resistance to puncture (1 to 4)
- B: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)



#### EN511:2006 Protective gloves against cold (X = Unrealized test)

- 1: Resistance to convective cold (from 1 to 4)
- 2: Resistance to contact cold (from 1 to 4)
- 1: Waterproof (0 or 1)

#### EN407:2020 Protective gloves against Heat (X = Unrealized test)

X: Flame spread resistance.



- X: Small splashes of molten metal (from 1 to 4)
- X: Large quantities of molten metal (from 1 to 4)



Item details								
Item details	Bar code	COLOUR	SIZE	9	À			
VV736BL09	3295249201265	Blue-Black	09	60	12			
VV736BL10	3295249201272	Blue-Black	10	60	12			
VV736BL11	3295249201289	Blue-Black	11	60	12			