

TG6250

The TG6250 provides an unmatched experience of durability and comfort by using the LXT yarn. It has an excellent soft handfeel, yet still provides level E cut resistance according to EN388:2016.

The crinkle latex coating and Life Extending Technology treatment make the TG6250 perfect for high cut risk tasks in wet, dry and oily conditions. It provides outstanding grip, whilst maintaining a high level of dexterity.



The LXT range is certified as carbon neutral from cradle to grave. This means that at no extra cost, your LXT glove has helped to lessen it's impact on the environment.





Ideal for



- Automotive
- Construction and utility
- Engineering and manufacturing
- Oil and gas
- Rail
- Mechanical and electrical
- Waste, recycling and local authority
- Glazing Manufacture & Installation



KEY

-  Dry
-  Wet
-  Heat
-  Oily
-  Cold
-  Chemical

EN 388	3X43E
Sizes	6-11
Liner	Polyester/Glass HPPE/Steel/ Nylon/Elastane
Gauge	15gg
Coating	X-Dura Crinkle Latex
Conditions	   

EN 388:2016  3 X 4 3 E	ASTM ANSI CUT LEVEL A5	EN 407:2020  X 1 X X X X
--	-------------------------------------	--

Qty/band	10 pairs
Qty/carton	100 pairs




Carbon neutral



Plastic free packaging



Conforms to EN 407:2020*



Resistance to oil & water



Reduction in cost in usage



Comfort & durability



Washable to 40°C
Certified up to 3 washes*



Reduction in waste & landfill